

Address

(34014) 94-23, Techno 2-ro, Yuseong-gu, Daejeon, Republic of Korea

Phone / Fax (Technology & Services)

+82 . 42 . 932 . 7586 / +82 . 42 . 932 . 7589

URL

www.klabkis.com

Contact

sales@klabkis.com





# The Smart Microvolume Spectrophotometer

NanoQ is wide wavelength microvolume spectrophotometer with morden design and user convenience UI. It supplies extremely fast and easy quantitative analysis of nucleic acid and protein by UV-VIS absorption spectrophotometry.

It provides microvolume sample measuring mode and cuvette measuring mode so can measure wide range of concentration.

You can easily set over 20 measuring mode.

Measuring Mode: Nucleic Acid(dsDNA, ssDNA, RNA), Protein(Lysozyme, BSA, IgG), OD600, etc.

## Compact

It is a small spectrophotometer featuring compact size and main unit control.

### Auto Pathlength

2

A user can conduct the measurement precisely because it can be automatically set the pathlength according to the concentration.

## Create User Menu

3

Can Add User Menu combined by user's most accessed measure mode.

#### 4 Quick Boot

There is no need for measurement standby since it does not require a lamp warming-up.







#### Full Spectrum Analysis

OPTIZEN NanoQ can measure the absorption spectrum UV-VIS (190 nm~850 nm) in seconds using by array type spectrophotometer technology with Xenon lamp and CMOS. sensor(2048 pixels). It also provide various algorithm like Peak/Valley detection.



#### Maximization of user friendliness

There is no need for a user manual since it provides a simple and intuitive user environment.

#### Cuvette Holder

It can measure protein and conduct cell counting. \*Cuvettes are only available in OPTIZEN NanoQ Plus.

#### **Date Management**

The measurement result can be saved or downloaded to a USB flash drive.

#### **LCD Touch Screen**

A user can easily operate the system using the intuitive LCD screen and touch functions.

#### Loading Guide

It helps even novice users to drop the sample easily and accurately on the loading spot.



#### Cuvette (Optional)

Provide pedestal and cuvette measuring mode at Optizen NanoQ Plus model. But, Do not provide cuvette measuring position at general OPTIZEN NanoQ model.



It does not need a separate computer since the main unit performs the control, and the measurement data can be saved in the equipment to improve the spatial utilization and economic efficiency.

The lightweight and small spectrophotometer features the dimensions of 216 x 290 x 153 mm and weight of 1.4 kg.

7.0 inch, 1280 x 800 HD color display device The built-in capacitive touch LCD panel helps users operate it easily and conveniently.









There is no need for a user manual since it provides a simple and intuitive user environment. The designated factor is set as the default value for each mode, and the input mode is provided to allow the users to set a factor value which is different from the default. Users can specify the factor ppropriate for the user preference, the lab environment, and the type of protein.

| Measurement menu configuration |           |            |
|--------------------------------|-----------|------------|
|                                | Menu      | Factor     |
| Nucleic Acid<br>(ng-cm/μl)     | dsDNA     | 50         |
|                                | ssDNA     | 33         |
|                                | RNA       | 40         |
|                                | miRNA     | 33         |
|                                | Custom    | Input      |
| Protein (g-cm/ℓ)               | BSA       | 1.5        |
|                                | SA        | 1.49, 1.72 |
|                                | lgG       | 0.71, 0.74 |
|                                | lgE Human | 0.65       |
|                                | Lysozyme  | 0.38       |
|                                | OD1       | 1          |
| OD600                          | OD600     | 1          |

#### Product



OPTIZEN NanoQ (Full-Spectrum)



**OPTIZEN NanoQ Lite** 

| Minimum Sample Size           |
|-------------------------------|
| Light source(s)               |
| Lifetime                      |
| Detector                      |
| Wavelength Range              |
| Wavelength Accuracy           |
| Spectral Resolution           |
| Absorbance Precision          |
| Absorbance Accuracy           |
| Absorbance Range              |
| Detection Limit (Microvolume) |
|                               |
|                               |
| Maximum Concentration         |
| Detection Limit (Cuvette)     |
| * Only OPTIZEN NanoQ Plus     |
|                               |
| Photometric Range             |
| Center Height (Z-height)      |
| Heating (Optional)            |
| Measurement Time              |
| Software Compatibility        |
| Display                       |
| Touchscreen                   |
| CPU                           |
| Storage                       |
| Glove Compatibility           |
| On-board Control              |
| Connectivity                  |
| Footprint (W x D)             |
| Weight (kg)                   |

| 1μL                                    | 1 μL   |  |
|--|--|--|
| Xenon flash lamp                       | LEDs   |  |
| Up to 10 years                         | Up to 10 years                                     |  |
| CMOS linear image sensor (2048 pixels) | Silicon photodiode                                 |  |
| 190 – 850 nm                           | 260, 280 nm / 600 nm(Cuvette) / 360 nm(Baseline)   |  |
| ±1nm                                   | ±1nm   |  |
| 1.0 nm (FWHM at Hg 253.7 nm)           | ≤ 8.0 nm   |  |
| 0.002 A (0.5 mm path) or 1%            | 0.002 A (0.5 mm path)                              |  |
| 3% (at 0.97A at 302 nm)                | 3% (at 1A at 280 nm)                               |  |
| 0.02 - 330 A (10mm equivalent)         | 0 – 200 A  |  |
| 2 ng/µL (dsDNA)                        | 2 ng/µL (dsDNA)                                    |  |
| 0.06 mg/mL (BSA)                       | 0.06 mg/mL (BSA)                                   |  |
| 0.003 mg/mL (IgG)                      | 0.003 mg/mL (lgG)                                  |  |
| 16,500 ng/µL (dsDNA), 400 mg/mL (BSA)  | 2,000 ng/µL(dsDNA), 60 mg/µL(BSA), 28.8 mg/µL(IgG) |  |
| 0.2 ng/µL (dsDNA)                      | -  |  |
| 0.006 mg/mL (BSA)                      | -  |  |
| 0.0003 mg/mL (IgG)                     | -  |  |
| 0 – 2 A                                | Range(10 mm Equivalent) – Cuvette: 0~2 A           |  |
| 15 mm                                  | 15 mm  |  |
| 37 °C                                  | -  |  |
| < 8 seconds                            | < 10 seconds                                       |  |
| Windows® 7 and 10                      | -  |  |
| 7-inch, 1280 x 800 HD color display    | 4.3-inch, 480 x 272 color display                  |  |
| Multipoint capacitive touch            | Resistive touch                                    |  |
| Octa Core ARM® Cortex™–A53 Processor   | -  |  |
| 32 GB Internal Storage                 | 8 GB Internal Storage                              |  |
| Compatible with lab gloves             | Compatible with lab gloves                         |  |
| Android™                               | Firmware   |  |
| 4 x USB ports, Ethernet, and RS-232    | 2 x USB ports, USB-B, and RS-232                   |  |
| 216 x 290 mm                           | 145 x 190 mm                                       |  |
| 3.0 kg                                 | 1.4 kg   |  |